

BTI-CYCLO

DESCRIPTION

Powerful IP65 full color LED cyclorama! Can be used for background and footlight on both in/outdoor stages.




FEATURES

- A very compact but powerful IP65 full color LED cyclorama with (HxV) 83°x51° beam angle.
- Colors background of in/outdoor theatre stages:
 - Uplighting to 3m high @1m distance
 - Uplighting to 6m high @2m distance
- Can also be fixed to the ceiling for downlighting!
- Perfect as footlight on in/outdoor theatre stages, to soften heavy shadows from overhead lighting!
- No more need for separate white and color projectors, BTI-CYCLO does it all:
 - Perfect WHITE with high CRI > 95Ra and CCT presets
 - Rich COLOR selection with color presets!
- The **CCS Color Calibration System** completely eliminates the color differences between different batches, while this cyclo also works perfectly together with our existing BT-THEATRE HD2:
 - The same CCT presets for white, ranging from 1800K to 10000K !
 - The same 48 calibrated color presets (according to LEE® / ROSCO® numbering)
- Based on a 160watt 6-color RGBALC LED-cluster (Red, Green, Blue, Amber, Lime, Cyan).
- Silent operation, thanks to passive cooling: NO cooling fan present!
- Can be used in full standalone mode without any need for DMX (museums, exhibition booths, ...).
- DMX-controlled: 6 different channel modes for maximum flexibility.
- RDM-functionality for easy remote setup: DMX addressing, channel mode, ...
- Flicker free TV-recordings thanks to the adjustable high LED-refresh rate!
- Two dimmer settings with different behavior & speed.
- Manual control for dimming, colors, CCT & zoom.
- OLED display for easy navigation through the settings menu!
- In case of DMX failure, you can choose between blackout and freeze mode.
- Lock function to avoid unwanted altering of the settings.
- Lightweight but rugged housing.
- PowerCON TRUE1 compatible in/outputs for easy daisy chaining.
- Thanks to a special conversion kit, the 3pin DMX in/outputs can be easily converted to 5pin XLR!




TECHNICAL SPECIFICATIONS

General : Dimensions (cm)	53 x 17 x 11 (WxDxH)
General : Weight (kg)	6
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	160
General : Color	black
General : Display	OLED
General : Fixation	included omega bracket
General : IP rating	outdoor
Control : Modes	standalone fixed, manual, DMX
Control : Protocol	DMX, RDM
Control : programmable	Yes
Control : upgradable software	Yes
Control : minimum DMX channels	3
Control : maximum DMX channels	20
Light : lamp socket	No
Light : Lux	56 (@5m)
Light : lamp	LED
Light : min. color temperature (K)	1800
Light : max. color temperature (K)	10000
Light : CRI	95
Light : colors	Amber, Lime, RGBALC
Light : mix colors	Yes
Light : functions	manual zoom
Light : max. beam angle (°)	83
Light : max. refresh rate (kHz)	25
Connections : input	3 pin XLR, 5 pin XLR, rdm, PowerCon® TRUE1 or compatible
Connections : output	3 pin XLR, 5 pin XLR, rdm, PowerCon® TRUE1 or compatible
Brand	BRITEQ
EANCode	5420025660518
SKU	B06051



YOUR DEALER



WWW.BRITEQ-LIGHTING.COM | WWW.FACEBOOK.COM/BRITEQ

BEGLEC NV HAS THE RIGHT TO CHANGE PRODUCTS AND SPECIFICATIONS WITH AND WITHOUT NOTICE. MAJOR AS WELL AS MINOR CHANGES CAN BE INVOLVED. THIS LEAFLET CAN CONTAIN ERRORS, THEREFORE WE ADVISE TO CONSULT YOUR LOCAL DEALER TO ENSURE THAT ACTUAL FEATURES AND SPECIFICATIONS MATCH YOUR REQUIREMENTS. COPYRIGHT © 2024 BY BEGLEC NV. ALL RIGHTS RESERVED.