

# EN12-45

TECHNICAL DATA | REV A

OBSIDIAN™  
CONTROL SYSTEMS



## KEY FEATURES

- RDM, Artnet and sACN support
- Factory and user presets for plug and play setups
- Line Voltage or POE powered
- 1.8" OLED Display with rotary knob
- 99 Internal cues with fade and delay time
- Customizable routing and merging options
- Remote configuration via internal webpage
- Contact closures for cue or preset recall
- Powder-coated aluminum rackmount housing

## SPECIFICATIONS

### MOUNTING

Rackmount

### CONNECTIONS

#### Front

- (12) RJ45 DMX/RDM optically isolated ports (ESTA Compliant)
- Ports are bidirectional for DMX In and Output
- Full color OLED display
- Encoder w. Push to Select / Exit Button

#### Back

- (2) Locking RJ45 Ethernet network In
- (10) Contact Closures (Terminal Block)
- Locking Power In/Thru

### PHYSICAL

- Length: 6.3 in. (160.8mm)
- Width: 19 in. (482.5mm)
- Height: 1.7 in. (44 mm)
- Weight: 4 lbs (1.82 kg)

### ELECTRICAL

- 100-240 V nominal, 50/60 Hz
- POE 802.3af

EN12-45

# ORDERING

## INCLUDED ITEMS

1.5m Locking power cable (EU or US version)

SKU

US #: NRE302

EU #: 1330000068

FS2123

