



SDI to HDMI Rack Module

Theatrix



#XVVRM-SDI2HDMI

The SDI to HDMI Rack Module is a unit option for the 8-Bay Reversible Rackmount Converter system. The module can be inserted in the 8-Bay Frame in either direction, allowing the inputs/outputs to be positioned either at the front or the back of the unit depending on the application. There are no exposed PCBs as all modules are enclosed, and therefore protected against static shock, dust and general wear and tear. Gold-plated, redundant spring pins with magnetic retention deliver DC power to the modules, meaning no messy cabling and external power bricks are needed.

Connections

Video Input

3G/HD/SD SDI BNC

Video Output

HDMI 1.2 type A with lock system
2 x 3G/HD/SD SDI BNC

Physical

Height

121.5 mm (4.78 in)

**Depth**

225 mm (8.85 in)

Width

41 mm (1.61 in)

Weight

710 g (1.56 lbs)

Power Requirements**Power Supply**

Reversible redundant power fed by TXVV-RF8 (8-Bay Rackmount Frame)

Power Consumption

20 W

Operational Voltage Range

12 VDC

Environmental**Relative Humidity**

0 % to 90 % non-condensing

Supported Signals**3G Format Support**

1080p50, 1080p59.94, 1080p60.

HD Format Support

720p50, 720p59.94, 720p60, 1080i50, 1080i59.94, 1080i60, 1080p23.98, 1080PsF23.98, 1080p24, 1080PsF24, 1080p25, 1080PsF25, 1080p29.97, 1080PsF29.97, 1080p30, 1080PsF30

SD Format Support



525/23.98 NTSC, 525/29.97 NTSC.625/25 PAL.

SDI Video Sampling

4:2:2 and 4:4:4

SDI Audio Sampling

Sample rate of 48 kHz and 24 bit.

SDI Color Space

YUV and RGB

SDI Auto Switching

Automatically detects incoming signal format.

SMPTE Standards

425 M Level A & B, 424 M Level A, 292 M, 259 M

In the box

Theatrix Reversible Module SDI to HDMI

Certifications



DESIGNED & MANUFACTURED
IN CANADA 