

# Product Detail Page



## PA-1200

Number: 17.0710

### 4-zone mono PA mixing amplifier

- 1 x 120W<sub>RMS</sub>
- Silent operation due to fanless cooling concept
- Chime, continuous sound and wailing sound, automatic mute, chime can also be activated via external momentary push-button, 2-tone chime or 4-tone chime (selectable)
- Bass, treble and master controls, level display via LEDs
- 15V phantom power for channels 2 and 3
- Insertions for various functions are available at option
- 482mm (19") rack installation with mounting frame PA-1200RM, available at option
- Mains operation and 24V emergency power operation



## Technical Facts

### General information

**Output power** 120W<sub>RMS</sub>

170W<sub>MAX</sub>

### Inputs

**Mic** 1.5mV/600Ω

**Line** 150mV/47kΩ

**Phono** 1mV/47kΩ (RIAA)

### Outputs

**Speakers** 1 x 4Ω , 1 x 8Ω ,

4 x 70/100V

**Preamplifier** 1V/1kΩ

**Frequency range** 80-15,000Hz

### Tone control

**Bass** ±10dB/100Hz

**Treble** ±10dB/10kHz

### S/N ratio

**Mic** > 60dB

**Line** > 70dB

**THD** < 1%

**Admiss. ambient temp.** 0-40 °C

**Power supply** 230V~/50Hz/280VA,

24V = /11A

**Dimensions** 420x122x350mm

**Weight** 13kg

### Inputs

**Mic** 1 x 6.3mm jack

**Mic/line** 3 x XLR, bal.

**Line** 1 x RCA L + R

**Phono/line** 1 x RCA L + R

**Telephone input** 1 x twin spring-load. term.



---

**Outputs**

---

**Tuner** 1 x twin spring-load. term.

---

**Mom. push-button for chime** 1 x twin spring-load. term.

---

**1 x preamplifier** 1 x 6.3mm jack

---

**Speakers** 7 x screw terminal

---

**Power supply**

---

**230V** 1 x 3-pin IEC jack

---

**24V DC current** screw terminals

---

