



Visit product page

D3000

L005745



D class high performance 2 channels amplifier, 2 x1500 w/8ohms , 2 x 3000w/4 ohms, XLR input, speakon output, led VU meter, temperature control fans, frequency response 20Hz - 34Kz,adjustable VPL, 10kg.

TECHNICAL DETAILS

Technical Specifications

8 ohms stereo power: 2x 1500 W.

4 ohms stereo power: 2x 3000 W.

Input connector: XLR female

Input impedance: 20k ohms balanced

Input Sensitivity: 0.77V 1.44V

Input CMRR: >80dB

Output connector: Speakon

Hum&Noise: >112dB

Damping Factor: >1000 @ 8 ohms

THD: <0.1% (20Hz-20kHz 1W)

Frequency Response: 20Hz-34KHz,(+0/-0.3dB, 1W/8ohms)

Level control: front level meter, from negative infinity to 0dB

Cooling: variable speed fans, front to rear airflow

Power Requirement: AC voltage 180-240V 50-60Hz

Amplifier dimensions: 88mmX488mmX438mm

Packing dimensions: 150mmX600mmX550mm


Net weight: 11.5 Kg.

Gross weight: 14.6 Kg.

PHOTOS



PRODUCT VIDEO



www.fos-lighting.eu

