



Visit product page



ICON PTZ HD

L005795

Professional PTZ HD Camera for live broadcasting, SONY 1/2.8" Progressive CMOS sensor 3.50 Megapixel, 20X optical zoom+58.7° view angle, Output: HDMI+SDI+USB+IP, RS232 In/out, RS422, 1080p, auto focus, IR remote, Minimum Illumination 0.1 lux.

TECHNICAL DETAILS

Specifications

20x optical zoom, Wide Angle: 58.7°

DUAL IP-Stream (H265/MJPEG). H265/H264 and MJPEG compression enabling FULL HD video stream by ultra low bandwidth over RTSP, TCP/IP, HTTP, etc

HDMI+SDI+IP+USB2.0+RS232(Input)+RS422/485+LINE IN (UVC control, NDI optional)

Can be controlled by RS232/RS485, or remote controller

Wall mounting, desktop or ceiling mounting.

Suitable for huddle, medium size and large conference room.

Technical Details

Resolution 1080p60/50, 1080i60/50, 1080p30/25

Signal System PAL/NTSC

Lens 20X optical zoom, f=4.7mm(wide)~94.0mm(far end) F1.6~F2.8

Horizontal View Angle 58.7° \times W \times 3.2° \times T

Pan 355°(max. speed: 80°/s)

Tilt -30° to +30° (max. speed: 60°/s)

Auto/Manual Focus System

S/N Ratio \geq 50db

9 preset positions by IR remote controller, 255 preset positions by Keyboard or PC

Minimum Illumination: 0.1Lux

Exposure Control: Auto/Manual/Priority AE/Exposure Compensation/Bright

Shutter Speed: 1/1000-1/10,000s
Gain: Auto/Manual
White Balance: Auto/Manual/ATW/One-click/Indoor/Outdoor
Image Effect: Full color/black and white/electronic flip
Video Output: HD HDMI, SDI,USB, IP
Other Output: Line In
Control Protocol: SONY VISCA, PELCO P/D
Control Mode: RS-232C, RS-422/485

Installation / Dimension

Power: 12V DC(10.8-13.0V DC)
Power Consumption Max.: 30W(DC 12V)
Operating Temperature: 0-40°C
Storage Temperature: -20-60°C
Camera Dimensions: (L)147 ×(W)147 ×(H)165 mm
Weight: 870 g
Color: Black

Packing Details

Carton box: 30 x 25 x 25 cm - 2 kg

PHOTOS



PRODUCT VIDEO




ACCESSORIES



ICON PTZ Controller

IP Joystick Controller, Lcd screen, 28 keys, Double



www.fos-lighting.eu

