

Eris® Studio 5

High-Definition Near Field Studio Monitors

Key Features

- 5.25-inch woven composite low-frequency driver
- 1-inch, ultra-low mass, silk-dome, high frequency driver
- 100° x 60° EBM waveguide provides a sweet spot
- Front-firing acoustic port for superior bass-frequency reproduction and optimized, resonance-suppressing internal bracing
- 80W, Class AB dual amplification
- 48 Hz to 20 kHz frequency response
- 102 dB Peak SPL (@ 1 meter)
- Acoustic Tuning Controls



The **Eris Studio 5** is a substantial update that builds on the reputation of its predecessors by offering deep lows and a wider, more controlled sweet spot so you'll hear every transient, detail, and breath in your recordings.

The custom-designed EBM (Elliptical Boundary Modeled) waveguide provides superior high-frequency response and wider 100-degree horizontal dispersion to create a broader sweet spot. Narrow vertical dispersion reduces reflections from your desk and a silk-dome tweeter ensures snappy, accurate transient reproduction.

The woven composite low-frequency driver offers Eris' signature tight, clear bass with plenty of punch. The ported enclosure maximizes bass response and allows the Eris Studio 5 to reach down to an astonishing 48 Hz. That's 10 Hz below previous models—with no subwoofer!

Flexible input options let you connect almost any line-level source, from mixers to audio interfaces and more. You'll have no problem hooking your Eris speakers up to virtually anything.

Sold Individually.

Technical specifications

Frequency Response	48 Hz to 20 kHz
Peak SPL	102 dB (@ 1M)
LF Amplifier Power	45W, Class AB
HF Amplifier Power	35W, Class AB
LF Driver	5.25-inch woven composite
HF Driver	1-inch, silk-dome
Inputs (1 each)	Balanced XLR Balanced ¼-inch TRS Unbalanced RCA
Controls	Volume High Frequency Low Frequency Acoustic Space Low Cut Power Saver
Dims (H x W x D)	11.48" x 8" x 8.78" (291.5mm x 203.2mm x 223mm)
Weight	11.46 lbs (5.2 kg)

Part Number	Description	UPC Code
2777500127	ERIS STUDIO 5	673454011641
2777503127	ERIS STUDIO 5 AU	673454011658
2777504127	ERIS STUDIO 5 UK	673454011689
2777506127	ERIS STUDIO 5 EU	673454011665
2777507127	ERIS STUDIO 5 JP	673454011672
2777514127	ERIS STUDIO 5 MX	673454012105