



Visit product page

## D4004

L005747



D class high performance 4 channels amplifier, 4 x900 w/8ohms , 4 x1800w/4 ohms, XLR input, speakon output, led VU meter, temperature control fans, frequency response 20Hz - 34Kz,adjustable VPL, 10kg.

### TECHNICAL DETAILS

#### Technical Specifications

8 ohms Stereo Power: 4x 900W.

4 ohms Stereo Power: 4x 1800W.

Input connector XLR: female.

Input impedance: 20k ohms balanced.

Input Sensitivity: 0.77V 1.44V.

Input CMRR: >80dB.

Output: connector Speakon.

Hum&Noise: >112dB.

Damping Factor: >1000 @ 8 ohms.

THD: <0.1% (20Hz-20kHz 1W).

Frequency Response: 20Hz-34KHz,(+0/-0.3dB, 1W/8ohms).

Level control: front level meter, from negative infinity to 0dB.

Cooling: variable speed fans, front to rear airflow.

Power Requirements: AC voltage 180-240V 50-60Hz.


Amplifier dimensions: 88mm x 490mm x 415mm.

Packing dimensions: 150mm x 600mm x 520mm.

Net weight(kg): 12.7

Gross weight(kg): 15.9

PHOTOS



[www.fos-lighting.eu](http://www.fos-lighting.eu)

